

DH-NVR5808/5816/5832


NVR de 8/16/32 Canales



Características

- Hasta el 8/16/32 canales con 1080p en tiempo real vista en vivo
- Decodificación dual codec H.264/MJPEG
- Resolución de hasta 5MP
- Max 160Mbps de ancho de banda entrante
- Salida de vídeo simultánea HDMI / VGA
- 08/16/16 canal de reproducción en tiempo real síncrono, interfaz RED
- 8/16/32 canal sincrónico vista previa en tiempo real, interfaz RED
- Soporte Multimarca cámaras de red: Dahua, Arecont Vision, AXIS, Bosch, Brickcom, Canon, CP Plus, Dynacolor, Honeywell, Panasonic, Pelco, Samsung, Sanyo, Sony, Videosec, Vivotek, etc
- Versión conformidad ONVIF 2.0
- Posicionamiento inteligente 3D con la cámara PTZ Dahua
- Soporte 8 discos duros SATA de hasta 32 TB, 1 eSATA hasta 16TB, 4 USB 2.0
- Monitoreo de red múltiple: Web, CMS (DSS / PSS) y DMSS

Conexion del sistema



* NVR5816 como ejemplo

DH-NVR5808/5816/5832

Especificaciones Técnicas

Model	DH-NVR5808	DH-NVR5816	DH-NVR5832
System			
Main Processor	Dual-core embedded processor		
Operating System	Embedded LINUX		
Video & Audio			
IP Camera Input	8 channel	16 channel	32 channel
Two-way Talk	1 channel Input, 1 channel Output, BNC		
Display			
Interface	1 HDMI, 1 VGA, 1TV		
Resolution	1920×1080, 1280×1024, 1280×720, 1024×768		
Display Split	1/4/8/9	1/4/8/9/16	1/4/8/9/16/25/32
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording		
Recording			
Compression	H.264 / MJPEG		
Resolution	5MP(2560×1920) / 3MP(2048×1536) / 1080P(1920×1080) / 720P(1280×720) / D1 (704×576/704×480) & etc.		
Record Rate	Max 128Mbps (eg. 16ch 5MP@8Mbps, 32ch 1080P@4Mbps & etc.)		
Bit Rate	48~ 8192kbps		
Record Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop		
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec		
Video Detection & Alarm			
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Buzzer & Screen tips		
Video Detection	Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank		
Alarm Input	8 channel	16 channel	16 channel
Relay Output	6 channel		
Playback & Backup			
Sync Playback	1/4/9	1/4/9/16	1/4/9/16
Search Mode	Time/Date, Alarm, MD & Exact search (accurate to second), Smart search		
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom		
Backup Mode	USB Device / eSATA Device / Internal SATA burner/ Network		
Network			
Ethernet	2 RJ-45 port (10/100/1000Mbps)		
Network Function	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, IP Search(Support Dahua IP camera, DVR, NVS and etc.)		
Max. User Access	20 users		
Smart Phone	iPhone, iPad, Android, Windows Phone		
Storage			
Internal HDD	8 SATA ports (8HDDs or 6HDDs+1CD/DVD-RW), up to 32TB, Raid (redundancy)		

DH-NVR5808/5816/5832

External HDD	1 eSATA port (Max 4 SATA HDDs), up to 16TB
Auxiliary Interface	
USB	4 ports (2 Rear), USB2.0
RS232	1 port, For PC communication & Keyboard
RS485	1 port, For PTZ control
General	
Power Supply	AC 100V~240V, 50/60Hz
Power Consumption	40W (without HDD)
Working Environment	-10°C~+55°C/10%~90%RH/86~106kpa
Dimension (W×D×H)	2U, 440mm×460mm×89mm
Weight	6KG (without HDD)